





D-IP SERIES

D-IP 55 RACK

SURFACE MOUNT OUTDOOR



HIGHLIGHTS

	Safety class rating IP55
	Available in heights from 22U up to 42U
	Robust Structure
	Secure Surface Mount

D-IP 55 FEATURES

- Safety class rating IP55 for Outdoor applications
- Available in heights from 22U up to 42U
- Available with 600mm and 800mm depth
- Front door: sealed, locked and strong
- Swing handle lock fitted front door
- Rear wall has a cable entry with protective cover
- Integrated air ventilation inlets ensure the entry of fresh air
- Hinged fan module protective cover with snap-on feature
- Full height galvanized steel 19" profiles
- 19" profiles marked with U height position
- Must be ordered with plinth for standing (sold separately)

PRODUCT OVERVIEW

D-IP 55 series Outdoor cabinets are designed for industrial applications. They are based on IP55 safety class and protected against water and dirt ingress.

D-IP 55 series are available in a range of heights and depths. Integrated air ventilation inlets ensure the entry of fresh air from both sides. Each cabinet is designed with strength, ease of use and aesthetics in mind. Fully adjustable front and rear profile rails of the cabinet, make this product extremely attractive to installers.

Each rack consists of up to 1.5 mm strong steel sheet material which ensures a very good stability as a robust steel construction. An extensive accessories portfolio for plinths, shelves, cable management, etc. will help to meet many requirements in daily use.



D-IP 55 RACK 600x450mm (WxD)

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (mm)	LOAD CAPACITY (mm)
DIP55604507UG	7	GREY	7035	470	600	450	30	100
DIP55604509UG	9	GREY	7035	558	600	450	32	100
DIP55604512UG	12	GREY	7035	691	600	450	36	100
DIP55604516UG	16	GREY	7035	868	600	450	40	100
DIP55604520UG	20	GREY	7035	1046	600	450	44	100

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (kg)	LOAD CAPACITY (kg)
DIP55604507UB	7	BLACK	9005	470	600	450	30	100
DIP55604509UB	9	BLACK	9005	558	600	450	32	100
DIP55604512UB	12	BLACK	9005	691	600	450	36	100
DIP55604516UB	16	BLACK	9005	868	600	450	40	100
DIP55604520UB	20	BLACK	9005	1046	600	450	44	100

D-IP 55 RACK 600x450mm (WxD) // Double Walled

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (mm)	LOAD CAPACITY (mm)
DIP55604507UG2	7	GREY	7035	470	600	450	40	100
DIP55604509UG2	9	GREY	7035	558	600	450	42	100
DIP55604512UG2	12	GREY	7035	691	600	450	46	100
DIP55604516UG2	16	GREY	7035	868	600	450	50	100
DIP55604520UG2	20	GREY	7035	1046	600	450	54	100

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (kg)	LOAD CAPACITY (kg)
DIP55604507UB2	7	BLACK	9005	470	600	450	40	100
DIP55604509UB2	9	BLACK	9005	558	600	450	42	100
DIP55604512UB2	12	BLACK	9005	691	600	450	46	100
DIP55604516UB2	16	BLACK	9005	868	600	450	50	100
DIP55604520UB2	20	BLACK	9005	1046	600	450	54	100



D-IP 55 RACK 600x600mm (WxD)

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (kg)	GROSS WEIGHT (kg)
DIP55606022UFSG2	22	GREY	7035	1242	600	600	74	77
DIP55606026UFSG2	26	GREY	7035	1420	600	600	82,5	87
DIP55606032UFSG2	32	GREY	7035	1687	600	600	97	101
DIP55606036UFSG2	36	GREY	7035	1865	600	600	106	110
DIP55606042UFSG2	42	GREY	7035	2132	600	600	120	125

D-IP 55 RACK 600x800mm (WxD)

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (kg)	GROSS WEIGHT (kg)
DIP55608022UFSG2	22	GREY	7035	1242	600	800	84	87
DIP55608026UFSG2	26	GREY	7035	1420	600	800	95	99
DIP55608032UFSG2	32	GREY	7035	1687	600	800	110	114
DIP55608036UFSG2	36	GREY	7035	1865	600	800	121	125
DIP55608042UFSG2	42	GREY	7035	2132	600	800	137,5	143

D-IP 55 RACK 800x800mm (WxD)

P/N	U	COLOR	RAL	HEIGHT (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (kg)	GROSS WEIGHT (kg)
DIP55808022UFSG2	22	GREY	7035	1242	800	800	93	96
DIP55808026UFSG2	26	GREY	7035	1420	800	800	104	108
DIP55808032UFSG2	32	GREY	7035	1687	800	800	126	131
DIP55808036UFSG2	36	GREY	7035	1865	800	800	141	146
DIP55808042UFSG2	42	GREY	7035	2132	800	800	164	170



PICTURES - DETAILED



TECHNICAL DRAWING - Surface Mount with Plinth

